



Becatech

Interconnective Power



**Vein end sleeve silver
(Adereindhuls)**

Technical Specification :

Material: copper.

Surface: tin-plated to protect against corrosion.

Characteristics: to DIN 46228, part 1 and similar.

Application :

For fine and superfine stranded conductors, e.g. to DIN EN 60228 class 5 and 6.

Optimal cable entry due to widened sleeve.



Becatech


Interconnective Power

Cross Section mm ²	Part No.	Dimension mm				Weight /1000 pcs. (kg)
		d1	d2	l	s	
0.25	695V	0.75	1.7	5	0.15	0.02
	697V	0.75	1.7	7	0.15	0.03
0.34	705V	0.85	1.8	5	0.15	0.02
	707V	0.85	1.8	7	0.15	0.03
0.5	71S6V	1.00	2.1	6	0.15	0.03
	71S8V	1.00	2.1	8	0.15	0.04
	71S10V	1.00	2.1	10	0.15	0.05
0.75	716V	1.20	2.3	6	0.15	0.04
	718V	1.20	2.3	8	0.15	0.05
	7110V	1.20	2.3	10	0.15	0.06
	7112V	1.20	2.3	12	0.15	0.08
	7115V	1.20	2.3	15	0.15	0.09
1	72S6V	1.40	2.5	6	0.15	0.04
	72S8V	1.40	2.5	8	0.15	0.06
	72S10V	1.40	2.5	10	0.15	0.07
	72S12V	1.40	2.5	12	0.15	0.08
	72S15V	1.40	2.5	15	0.15	0.10
1.5	726V	1.70	2.8	6	0.15	0.05
	727V	1.70	2.8	7	0.15	0.06
	728V	1.70	2.8	8	0.15	0.07
	7210V	1.70	2.8	10	0.15	0.09
	7212V	1.70	2.8	12	0.15	0.10
	7215V	1.70	2.8	15	0.15	0.13
	7218V	1.70	2.8	18	0.15	0.15
	7220V	1.70	2.8	20	0.15	0.17
2.5	737V	2.20	3.4	7	0.15	0.08
	738V	2.20	3.4	8	0.15	0.09
	7310V	2.20	3.4	10	0.15	0.11
	7312V	2.20	3.4	12	0.15	0.13
	7315V	2.20	3.4	15	0.15	0.17
	7318V	2.20	3.4	18	0.15	0.20
	7320V	2.20	3.4	20	0.15	0.22
4	748V	2.80	4.0	8	0.20	0.14
	749V	2.80	4.0	9	0.20	0.16
	7410V	2.80	4.0	10	0.20	0.17

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech


Interconnective Power

	7412V	2.80	4.0	12	0.20	0.20
	7415V	2.80	4.0	15	0.20	0.27
	7418V	2.80	4.0	18	0.20	0.32
	7420V	2.80	4.0	20	0.20	0.35
6	7510V	3.50	4.7	10	0.20	0.23
	7512V	3.50	4.7	12	0.20	0.27
	7515V	3.50	4.7	15	0.20	0.34
	7518V	3.50	4.7	18	0.20	0.40
	7520V	3.50	4.7	20	0.20	0.45
	7525V	3.50	4.7	25	0.20	0.56
10	7610V	4.50	5.8	10	0.20	0.27
	7612V	4.50	5.8	12	0.20	0.33
	7615V	4.50	5.8	15	0.20	0.41
	7618V	4.50	5.8	18	0.20	0.49
	7620V	4.50	5.8	20	0.20	0.55
	7625V	4.50	5.8	25	0.20	0.68
16	7712V	5.80	7.5	12	0.20	0.43
	7715V	5.80	7.5	15	0.20	0.53
	7718V	5.80	7.5	18	0.20	0.60
	7720V	5.80	7.5	20	0.20	0.70
	7725V	5.80	7.5	25	0.20	0.87
	7732V	5.80	7.5	32	0.20	1.11
25	7812V	7.30	9.5	12	0.20	0.80
	7815V	7.30	9.5	15	0.20	0.99
	7818V	7.30	9.5	18	0.20	1.18
	7820V	7.30	9.5	20	0.20	1.31
	7825V	7.30	9.5	25	0.20	1.63
	7828V	7.30	9.5	28	0.20	1.82
	7832V	7.30	9.5	32	0.20	2.07
35	7912V	8.30	11.0	12	0.20	0.90
	7915V	8.30	11.0	15	0.20	1.12
	7918V	8.30	11.0	18	0.20	1.34
	7920V	8.30	11.0	20	0.20	1.48
	7922V	8.30	11.0	22	0.20	1.63
	7925V	8.50	11.0	25	0.20	1.80
	7930V	8.30	11.0	30	0.20	2.20
	7932V	8.50	11.0	32	0.20	2.35
50	8018V	10.3	13.0	18	0.30	1.69

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

	8022V	10.3	13.0	22	0.30	2.05
	8025V	10.3	13.0	25	0.30	2.32
	8030V	10.3	13.0	30	0.30	2.77
	8032V	10.3	13.0	32	0.30	2.95
70	8122V	12.7	15.0	22	0.40	3.31
	8125V	12.7	15.0	25	0.40	3.75
	8130V	12.7	15.0	30	0.40	4.48
	8132V	12.7	15.0	32	0.40	4.78
95	8225V	14.7	17.0	25	0.40	4.32
	8230V	14.7	17.0	30	0.40	5.17
	8232V	14.7	17.0	32	0.40	5.17
	8234V	14.7	17.0	34	0.40	5.84
120	8330V	16.7	19.0	30	0.50	7.35
	8332V	16.7	19.0	32	0.50	7.83
	8334V	16.7	19.0	34	0.50	8.32
	8338V	16.7	19.0	38	0.50	9.28
	8340V	16.7	19.0	40	0.50	9.76
150	8432V	18.7	21.0	32	0.50	8.75
	8434V	18.7	21.0	34	0.50	9.28
	8438V	18.7	21.0	38	0.50	10.36
	8440V	18.7	21.0	40	0.50	10.89
185	8532V	20.2	23.5	32	0.60	11.38
	8540V	20.2	23.5	40	0.60	14.17
240	8634V	23.0	26.0	34	0.50	11.25
	8640V	23.0	26.0	40	0.50	13.23

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079