



Becatech

Interconnective Power



**Rubber insulated control cable
(H05RN-F)**

Cable Structure :

Conductor: flexible bare copper.
Insulation: rubber (EPR) EI4.
Outer sheath : rubber (CR) EM2.

Technical Specification :

Rated conductor temperature:
Rated temperature fixed installation:
Flame retardant according to IEC 60332-1-2.

Application :

For the connection of electrical appliances with low mechanical stress in household, kitchen, office.
NOT suitable for permanent outdoor use.

| Core x mm ² | Overall Diameter mm | Cu Mass mm | Weight (kg) |
|---------------------------|---------------------------|------------------|----------------|
| 2x0.75 | 6.2 | 14.4 | 60 |
| 2x1 | 6.8 | 19.0 | 70 |
| 3g0.75 | 6.6 | 21.6 | 80 |
| 3g1 | 7.2 | 29.0 | 90 |
| 4x0.75 | 8.8 | 29.0 | 76 |
| 4g0.75 | 8.8 | 29.0 | 76 |

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079