



Becatech

Interconnective Power



Industrial rubber control cable (H05RR-F)

Cable Structure :

Conductor: bare copper.
Insulation : vulcanized rubber mixture EI4.
Outer sheath: vulcanized rubber mixture EM3.

Technical Specification :

Rated temperature flexible installation: -30°C to 60°C.
Rated temperature fixed installation: -30°C to 60°C.
Rated bending radius flexible installation: +/- 7.5 x ϕ .
Flame retardant according to IEC 60332-1.

Application :


Lightweight rubber hose for connection of electrical appliances at low to medium mechanical stress in the home and office in dry and wet rooms.
NOT suitable for permanent outdoor use.

Core x mm ²	Overall Diameter mm	Cu Mass mm	Weight (kg)
2x0.75	6.2	14.4	60
2x1	6.8	19.0	70
2x1.5	8.2	29.0	100
2x2.5	9.7	48.0	150
3g0.75	6.6	21.6	80
3g1	7.2	29.0	90
3g1.5	8.8	43.0	130
3g2.5	10.2	72.0	180
4g0.75	7.2	29.0	90
4g1	7.8	38.0	110

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

4g1.5	9.8	58.0	170
4g2.5	11.2	96.0	230
5g0.75	9.9	36.0	113
5g1.5	10.7	72.0	190
5g2.5	12.5	120.0	280

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079