



Becatech

Interconnective Power



Heavy duty rubber power cable (NSShÖU-O)

Cable Structure :

Conductor: flexible bare copper.
Insulation: EPR.
Outer sheath: polychloroprene.

Technical Specification :

Rated temperature flexible installation: -25°C to 80°C.
Rated temperature fixed installation: -40°C to 80°C.
Rated bending radius flexible installation: 10 x ϕ .
Fire behaviour according to IEC 60332-1.

Application :

In dry, damp and wet environments and outdoors in heavy mechanical loads, for heavy equipment and tools, construction sites, industrial, mining, quarrying and underground mining.

Core x mm ²	Overall Diameter Mm	Cu Mass	Weight (kg/km)
2x1.5	14.5	29.0	163
2x2.5	15.8	48.0	210
3x2.5	16.5	72.0	255
4x2.5	19.0	96.0	328
2x4	17.3	77.0	270
3x4	20.0	115.0	361
5x4	23.0	192.0	501
2x6	22.0	115.0	280
3x6	22.0	173.0	447

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079



Becatech

Interconnective Power

3x10	25.0	288.0	695
1x16	13.5	154.0	229
2x16	27.0	307.0	740
1x25	16.5	240.0	350
2x25	31.0	480.0	975
1x35	18.0	336.0	446
1x50	20.0	480.0	618
1x95	25.0	912.0	1082
1x120	27.5	1152.0	1350
1x150	30.0	1440.0	1660
1x185	32.0	1776.0	2067
1x240	36.0	2304.0	2621
1x300	41.0	2880.0	3320

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079