



Becatech

Interconnective Power



Thin-walled flexible shrink tubing (Heat shrink tubing)

Technical Specification :

Shrinking tube type: H-2(3X)
Flame retardant according to VW-1.
Self-extinguishing.
Rated temperature: -55°C to 125°C.
Minimum shrink temperature: 70°C.
Minimum full shrink temperature: 0°C to 100°C.
Length shrinkage: 0 to 10% maximum.
Quality class material: crosslinked polyolefin.

Length m	Delivery Inner Diameter mm Minimum	After shrinking Inner Diameter mm Maximum	After Shrink: Wall thickness mm Minimum	Available Colors
150	1.5	0.5	0.45	BK/TT
150	3.0	1.0	0.55	BK/TT
75	4.8	1.5	0.60	BK/TT
75	6.4	2.0	0.65	BK/TT
75	9.5	3.0	0.75	BK/TT
50	12.7	4.0	0.80	BK/TT
30	19.1	6.0	0.90	BK/TT
30	25.4	8.0	1.20	BK/TT
30	39.0	13.0	1.25	BK/TT

Becatech B.V.
Middenweg 18
3930 Hamont-Achel

info@becatech.be
www.becatech.be
+32 (0)11 19 29 45

IBAN BE89363217265185
VAT BE0777.903.079
CoC 0777.903.079